



VGRCB-15CPF / VGFCB-15CPF



The VGRCB-15CPF provides 15 contacts for coax, power or a combination of both contact styles. Coax contacts are provided for signals up to 500Mhz and power signals up to 30 Amps / 250 VAC. Proper alignment is ensured by two precision alignment pins per block. Two shoulder mounting screws per VGR block allow the block to float in the receiver. Contacts, blocks and cables sold separately.

Coax Contact Pair Specifications

Voltage 250VAC Current 1.5 Amps Contact Resistance $6m\Omega$ Capacitance 5pf Inductance 3nH Bandwidth 500Mhz Durability 25,000 Cycles Coax Connection Type Crimp

Power Contat Pair Specifications

Power Contact 30 Amps

Ordering Information:

Receiver Module: VGRCB-15CPF Ref No (910) Fixture Module: VGFCB-15CPF Ref No (911) 36" Receiver Coax Cable Assy. CR-CA50RG174-36
Receiver Power Contact CR-610116102 12 AWG Fixture Power Contact CF-610115-103

Accessories

Receiver Contact Extraction Tool VGRXT Fixture Contact Extract Tool VGFXT Receiver Alignment Pin Installation Tool B32503

For more information about VG Mass Interconnect products: Contact your Local Sales Representative at www.ect-cpg.com/principal-offices Visit ECT Online at www.ect-cpg.com/vg-mass-interconnect-products

